

### Plexiglas® Frosted Acrylic Sheet

#### 1. Product details

Plastic sheet products Usage:

Chemical characterization: <= 100% Acrylic copolymers

<=10% Methyl Methacrylate with styrene copolymers

#### Hazards identification

This material is classified as not hazardous under OSHA regulations. Under normal conditions of use, this product is not expected to create any unusual industrial hazards. Irritating gases/fumes may be given off during burning or thermal decomposition. Contact with hot material will cause thermal burns.

#### 3. First aid measures

Inhalation: Move subject to fresh air.

Skin contact: If molten material contacts skin, cool rapidly with cold water

and obtain medical attention for thermal burn.

Eye contact: Flush eves with plenty of water for at least 15 minutes. Call a

physician.

Ingestion: If swallowed, do not induce vomiting. Get medical attention.

#### 4. Fire - fighting measures

Suitable extinguishing measures: Water spray, carbon dioxide, dry chemical, foam.

Fire fighters and others who may be exposed to products of Protective equipment:

combustion should wear full fire fighting turn out gear and self-

contained breathing apparatus.

Heated material can form flammable vapors with air. When Fire and explosion hazards:

burned, the following hazardous products of combustion can occur: carbon oxides, hazardous organic compounds

#### Accidental release measures

Personal precaution, environmental precaution, and methods for cleaning up: Pick up transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste

characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

#### 6. Handling and storage

Handling: Avoid breathing dust. Avoid breathing processing fumes or

vapors. Handle in accordance with good industrial hygiene

and safety practices.





Storage: Avoid extreme temperatures. Keep in a cool, dry place. Store

away from sources of heat and light.

### 7. Exposure control

**Airborne Exposure Guidelines** 

Octadecanoic acid (57-11-4)
US ACGIH Threshold limit values

Time weighted average 10 mg/m3

Methyl methacrylate (80-62-6)

US. ACGIH Threshold Limit Values

Time weighted average 50 ppm Short Term Exposure Limit (STEL): 100 ppm

PEL: 100 ppm (410 mg/m3)

8. Physical and chemical properties

Physical state: Solid sheets

Color: Colorless

Odor: Odorless

pH: Not applicable

Melting point: No data available

Boiling point: No data available

Decomposition temperature: >572°F (>300°C)

Flash point: Not applicable

Auto-ignition temperature: 860°F (460°C)

Evaporation rate: Not applicable

Vapor pressure: Not applicable

Vapor density: Not applicable

Solubility: Insoluble

9. Stability and reactivity

Stability: This material is chemically stable under normal and

anticipated storage, handling, and processing conditions.

Hazardous reactions: None known.

Materials to avoid: None under normal conditions of use.





Hazardous decomposition products: Thermal decomposition giving flammable and toxic products:

carbon oxides, acrylates, methacrylate.

Conditions to avoid: Avoid flames, welding arcs, potential ignition sources, or other

high temperature sources which induce thermal

decomposition.

#### 10. Toxicological information

This product should not be harmful under normal conditions of use.

Inhalation: 4 h acute toxicity estimate > 40 mg/l

Skin contact: Not a skin sensitizer. Buehler Test (guinea pig). No skin

allergy was observed.

Ingestion: Unlikely to be harmful by ingestion under ambient

temperature.

Eye contact: This product in the form of dust can be irritating to the eyes. At

high temperature, products of thermal decomposition can be

irritating to the eyes.

### 11. Ecological information

This product is a solid, inert product with low volatility, and is essentially insoluble in water.

Ecotoxicity: No data are available.

Mobility: Due to the solid nature of this product, it should have low

mobility in soil.

Persistence & degradability: This product is non-biodegradable.

Bioaccumulation: This solid product has a low potential for bioaccumulation.

Effect in sewage plants: May be separated mechanically.

#### 12. Disposal considerations

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental





permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

### 13. Transport information

Not subject to national and international regulations on the transport of dangerous goods.

14	Rea	ulator	rv inf	orma	tion
	1700	diato		OHILL	

Canadian Domestic Substances List All components of this product are on the Canadian DSL.

Toxic Substances Control Act: The components of this product are all on active TSCA

Inventory.

China Inventory of Existing Chemical

Substances in China:

Conforms

Japan Existing and New Chemical

Substances Inventory

Conforms

Korean Existing Chemicals Inventory Conforms

Philippines Inventory of Chemicals and

**Chemical Substances** 

Conforms

Australia Inventory of Chemical

Substances

Conforms

United States Federal Regulations

SARA Title III Section 302 Extremely

**Hazardous Chemicals** 

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible

concentrations.

SARA Title III - Section 311/312 Hazard

Categories:

No SARA Hazards

SARA Title III - Section 313 Toxic

Chemicals:

2-Propenoic acid, ethyl ester [CAS#140-88-5]

De minimis concentration: 0.1%

Reportable threshold: 10,000 lbs (otherwise used)

25,000 lbs (manufacturing and processing)

CERCLA Reportable Quantity

Methyl methacrylate

[CAS#80-62-6] – reportable quantity: 1,000 lbs

2-Propenoic acid, ethyl ester

[CAS#140-88-5] – reportable quantity: 1,000 lbs





<u>United States - State Regulations</u>

New Jersey Right to Know

No components are subject to the New Jersey Right to Know

Act.

Pennsylvania Right to Know

Chemical NameCAS-No.Acrylic copolymersProprietaryMethyl methacrylate - styrene copolymersProprietaryMethyl methacrylate80-62-62-Propenoic acid, ethyl ester140-88-52-methylpropan-2-ol75-65-0

Environmentally hazardous substances
Methyl methacrylate
2-Propenoic acid, ethyl ester
2-methylpropan-2-ol

CAS-No.
80-62-6
140-88-5
75-65-0

<u>Special hazardous substances</u>
2-Propenoic acid, ethyl ester

CAS-No.
140-88-5

California Prop. 65 WARNING! This product contains a chemical known to the State of

California to cause cancer.

<u>Chemical name</u>

Benzene, ethenyl2-Propenoic acid, ethyl ester

CAS-No.
100-42-5
140-88-5

#### 15. Other information

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Grades: This SDS covers TS, P-95, and DP-95 grades of this product.

SDS Prepared by: A&C Plastics

The information presented herein is believed to be factual and reliable. It is offered in good faith, but without guarantee, since conditions and methods for the use of our products are beyond our control. We recommend that the prospective user determine the suitability of our products and these suggestions before adopting them on a commercial scale.

