# Plexiglas® MC Acrylic Sheet

## 1. Product details

Usage:

Plastic sheet products

Chemical characterization:

<= 100% Acrylic copolymers

### 2. Hazards identification

This material is classified as not hazardous under OSHA regulations. Under normal conditions of use, this product is not expected to create any unusual industrial hazards. Irritating gases/fumes may be given off during burning or thermal decomposition. Contact with hot material will cause thermal burns.

3. First aid measures	
Inhalation:	Move subject to fresh air.
Skin contact:	If molten material contacts skin, cool rapidly with cold water and obtain medical attention for thermal burn.
Eye contact:	Flush eyes with plenty of water for at least 15 minutes. Call a physician.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention.
4. Fire – fighting measures	
Suitable extinguishing measures:	Water spray, carbon dioxide, dry chemical, foam.
Protective equipment:	Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear and self- contained breathing apparatus.
Fire and explosion hazards:	Heated material can form flammable vapors with air. When burned, the following hazardous products of combustion can occur: carbon oxides, hazardous organic compounds
5. Accidental release measures	

Personal precaution, environmental precaution, and methods for cleaning up: Pick up transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

### 6. Handling and storage

Handling:

Avoid breathing dust. Avoid breathing processing fumes or vapors. Handle in accordance with good industrial hygiene and safety practices.



Storage:

Avoid extreme temperatures. Keep in a cool, dry place. Store away from sources of heat and light.

### 7. Exposure control

#### **Airborne Exposure Guidelines**

US ACGIH Threshold limit values Time weighted average, respirable Time weighted average, inhalable

US. OSHA Table Z-3 (29 CFR 1910.1000) Time weighted average, respirable Form: Total Dust Form: Respirable fraction Form: time weighted average 3 mg/m3 10 mg/m3

15millions of particles per cubic ft of air 50millions of particles per cubic ft of air 5 mg/m3 15 mg/m3

#### 8. Physical and chemical properties

Physical state:	Solid sheets
Color:	Colorless
Odor:	Odorless
pH:	Not applicable
Melting point:	No data available
Boiling point:	No data available
Decomposition temperature:	>572°F (>300°C)
Flash point:	Not applicable
Auto-ignition temperature:	860°F (460°C)
Evaporation rate:	Not applicable
Vapor pressure:	Not applicable
Vapor density:	Not applicable
Solubility:	Insoluble
9. Stability and reactivity	
Stability:	This material is chemically stable under normal and anticipated storage, handling, and processing conditions.
Hazardous reactions:	None known.

Materials to avoid:

None under normal conditions of use.





Hazardous decomposition products:

Thermal decomposition giving flammable and toxic products: carbon oxides, acrylates, methacrylate, hazardous organic compounds.

Conditions to avoid:

Avoid flames, welding arcs, potential ignition sources, or other high temperature sources which induce thermal decomposition.

### 10. Toxicological information

This product should not be harmful under normal conditions of use.

Inhalation:

Skin contact:

Ingestion:

Eye contact:

4 h acute toxicity estimate > 40 mg/l (vapor)

Not a skin sensitizer. Buehler Test (guinea pig). No skin allergy was observed.

Unlikely to be harmful by ingestion under ambient temperature.

This product in the form of dust can be irritating to the eyes. At high temperature, products of thermal decomposition can be irritating to the eyes.

### 11. Ecological information

This product is a solid, inert product with low volatility, and is essentially insoluble in water.

Ecotoxicity:

Mobility:

Persistence & degradability:

**Bioaccumulation:** 

\_\_\_\_\_

No data are available.

Due to the solid nature of this product, it should have low mobility in soil.

This product is non-biodegradable.

This solid product has a low potential for bioaccumulation.

Effect in sewage plants:

May be separated mechanically.

### 12. Disposal considerations

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental



permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

### **13. Transport information**

Not subject to national and international regulations on the transport of dangerous goods.

#### 14. Regulatory information Canadian Domestic Substances List All components of this product are on the Canadian DSL. **Toxic Substances Control Act:** The components of this product are all on active TSCA Inventory. Conforms China Inventory of Existing Chemical Substances in China: Japan Existing and New Chemical Conforms Substances Inventory Korean Existing Chemicals Inventory Conforms Philippines Inventory of Chemicals and Conforms **Chemical Substances** Australia Inventory of Chemical Conforms Substances The components in this product are either not SARA Section **United States Federal Regulations** SARA Title III Section 302 Extremely 302 regulated or regulated but present in negligible Hazardous Chemicals concentrations. SARA Title III - Section 311/312 Hazard No SARA Hazards Categories: SARA Title III - Section 313 Toxic 2-Propenoic acid, ethyl ester [CAS#140-88-5] Chemicals: De minimis concentration: 0.1% Reportable threshold: 10,000 lbs (otherwise used) 25,000 lbs (manufacturing and processing) **CERCLA Reportable Quantity** Methyl methacrylate [CAS#80-62-6] - reportable quantity: 1,000 lbs 2-Propenoic acid, ethyl ester [CAS#140-88-5] - reportable quantity: 1,000 lbs



United States – State Regulations	
New Jersey Right to Know	No components are subject to the New Jersey Right to Know Act.
Pennsylvania Right to Know	
<u>Chemical Name</u>	<u>CAS-No.</u>
Acrylic copolymers	Proprietary
Methyl methacrylate	80-62-6
2-Propenoic acid, ethyl ester	140-88-5
Environmentally hazardous substances	CAS-No.
Methyl methacrylate	80-62-6
2-Propenoic acid, ethyl ester	140-88-5
Special hazardous substances	CAS-No.
2-Propenoic acid, ethyl ester	140-88-5
California Prop. 65	WARNING! This product contains a chemical known to the State of California to cause cancer.
Chemical name	CAS-No.
2-Propenoic acid, ethyl ester	140-88-5

## **15. Other information**

### Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.H315 Causes skin irritation.H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

SDS Prepared by: A&C Plastics

The information presented herein is believed to be factual and reliable. It is offered in good faith, but without guarantee, since conditions and methods for the use of our products are beyond our control. We recommend that the prospective user determine the suitability of our products and these suggestions before adopting them on a commercial scale.

