

Hygard BR1000 PRODUCT DETAILS

Ballistic Glazing - Level 2

Hygard BR 1000 ballistic grade sheet is a 1.000", 4-ply polycarbonate laminate that meets the UL 752 Level 2 rating for .357 Magnum ballistic attack and HP White TP 0500 Level IV. Unlike glass-clad products, this all-polycarbonate laminate resists spalling and white-out after repeated high force and ballistic impacts, an advantage in maintaining visibility of a threat during an attack. All Hygard products incorporate Tuffak polycarbonate sheet produced for high optical quality in security glazing laminates. Exterior surfaces have a proprietary Tuffak AR hardcoat that facilitates cleaning and resists marring, chemical attack, and graffiti. Hygard BR1000 sheet has a seven year Limited Product Warranty against coating failure, yellowing, and hazing. The terms of the warranty are available upon request.

APPLICATIONS


Government and detention facilities, banks, heavy equipment glazing, specialty retailers, 24 hour convenience stores, cash transaction windows.

Typical Properties*	
Property	Values
Gauge / Tolerance	1.05 in ± 5%
Weight	6.5 lbs / sq ft
Shading Coefficient	0.85
U-Value	0.60
Light Transmission	72%

*Typical properties are not intended for specification purposes

Product Performance Ratings
BALLISTIC UL 752 Level 2 (.357 Magnum jacketed lead soft point)
FORCED ENTRY & CONTAINMENT ASTM F 1233.08 Class 5 Body Passage ASTM F 1233.08 Class 2.4 Contraband Passage ASTM F 1915.03 Grade 1 H.P. White TP 0500.03 Level IV Sequence 43
AGENCY INFORMATION UL File: BP6864 Combustibility Class CC1 Miami-Dade NOA 12-0605.05

Hygard® BR1000
Sheet Construction



Glazing Recommendations

- Structural security framing systems with equal or greater forced entry and/or ballistics ratings as the selected Hygard laminate are recommended
- Hygard laminate should be cut to allow for a minimum of 1" edge engagement in the frame with sufficient rabbet depth for material expansion (approx. 1/16"/ft.)
- Use wet or dry sealants/gaskets that are compatible with polycarbonate
- Remove protective masking after glazing operations are completed and before prolonged exposure to direct sunlight, moisture, or high temperature

Glazing Recommendations

Standard Sheet Size

48" x 60", 48" x 72", 38"x96",
48"x96", 60"x72", 60"x96"

Product Specification

Hygard BR1000 polycarbonate laminate.
Four-ply, clear Tuffak polycarbonate sheet
constructed as follows:

- 1/8" Tuffak AR-1 abrasion resistant surface
- Polyurethane bonding interlayer
- 3/8" Tuffak polycarbonate sheet
- Polyurethane bonding interlayer
- 3/8" Tuffak polycarbonate sheet
- Polyurethane bonding interlayer
- 1/8" Tuffak AR-1 abrasion resistant surface