

OP2 Material Safety Data Sheet



Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

1. Chemical Product and Company Identification

ACRYLITE® - Special Products

The information of this material safety data sheet applies to the following product groups:

ACRYLITE® Reflections Acrylic Sheet, ACRYLITE® HEATSTOP FF, ACRYLITE® Radiant Acrylic Sheet, ACRYLITE® Sterling Acrylic Sheet, ACRYLITE SUNACTIVE® GP / FF, ACRYLITE® MULTICOLOR Acrylic Sheet, ACRYLITE® Fluorescent, ACRYLITE® 237 Acrylic Sheet, ACRYLITE® OP-4 Acrylic Sheet, ACRYLITE® GP F Acrylic Sheet, ACRYLITE® GP FL Acrylic Sheet, ACRYLITE® GP FLW Acrylic Sheet, ACRYLITE® BR2 Acrylic Sheet, ACRYLITE® BRT GAR Acrylic Sheet, ACRYLITE® BR Acrylic Sheet, ACRYLITE® BR GAR Acrylic Sheet, ACRYLITE® Securus™ Acrylic Sheet, ACRYLITE® Securus™ GAR Acrylic Sheet, ACRYLITE® OP-1 Acrylic Sheet, ACRYLITE® OP-2 Acrylic Sheet, ACRYLITE® OP-2 P-95 Acrylic Sheet, ACRYLITE® OP-3 Acrylic Sheet, ACRYLITE® AR OP-3 Acrylic Sheet, ACRYLITE® OP-3 P-99 Acrylic Sheet, Aviation Grades: ACRYLITE® GMS Acrylic Sheet, ACRYLITE® GMU Acrylic Sheet, ACRYLITE® 249 Acrylic Sheet

Supplier:

Evonik CYRO LLC
379 Interpace Parkway
Parsippany, NJ 07054-0677

Product Information Number 1-207-490-4242
24 Hour Emergency Number, CHEMTREC 1-800-424-9300

Product Use: acrylic glass, building glazing, protective glazing, store construction, trade-fair booth design, light advertising, displays, mirror, aircraft transparency, Industrial Use

2. Composition/Information on Ingredients

This material is classified as not hazardous under OSHA regulations.

<u>Ingredients</u>	<u>CAS Reg. No.</u>	<u>Weight %</u>
acrylic copolymer	trade secret	100

NJTSR # 56705700001-6896 P

See Section 8, Exposure Controls/Personal Protection

3. Hazards Identification


Emergency Overview



Service. It's what we deliver.

1.800.231.4175 www.acplasticsinc.com

OP2 Material Safety Data Sheet



Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

Color: colorless or colored
Appearance: sheets
Odor: odorless

Under normal conditions of use, this product is not expected to create any unusual industrial hazards.

Primary Routes of Exposure

Eye contact (if exposed to chips)

Potential Health Effects

Inhalation

No hazard expected in normal use.

Eye Contact

No hazard expected in normal use.

Material can cause the following:

- mechanical irritation

Skin Contact

Material can cause the following:

- cuts (when using cut sheets)

Ingestion

No hazard expected in normal use.

Potential Environmental Effects

See SECTION 12, Ecological Information

4. First Aid Measures

First Aid Procedures

Inhalation

No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

Eye Contact

If mechanical irritation occurs flush eyes thoroughly with a large amount of water, consult a physician if irritation persists. (possible during machining processes)

Skin Contact

No specific treatment is necessary since this material is not likely to be hazardous.

Ingestion

Ingestion is not considered a potential route of exposure.

5. Fire-Fighting Measures


Flash point	> 250 °C (ASTM D1929-68) > 482 °F (ASTM D1929-68)
Autoignition Temperature	> 400 °C (ASTM D1929-68) > 752 °F (ASTM D1929-68)
Lower explosion limit	not applicable
Upper explosion limit	not applicable



Service. It's what we deliver.

1.800.231.4175 www.acplasticsinc.com

OP2 Material Safety Data Sheet



Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

OSHA Flammability Classification none

Other Flammable Properties

Use water spray to cool containers exposed to fire.

Extinguishing Media

Use the following extinguishing media when fighting fires involving this material:

water spray - foam - dry chemical - carbon dioxide

Fire Fighting Procedures

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Procedures

Collect material and place in a disposal container. Obey relevant local, state, provincial and federal laws and regulations.

See Material Safety Data Sheet section 8, Exposure Controls/Personal Protection.

7. Handling and Storage

Handling

During thermal processing and/or machining local exhaust ventilation at processing machines is necessary.

Storage

Storage: dry.

8. Exposure Controls/Personal Protection

Engineering Controls (Ventilation)

If use operations generate dust, use adequate ventilation.

Respiratory Protection

A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Eye Protection

goggles for machining operations

Hand Protection

protective gloves against mechanical risks

Other Protective Equipment

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

OP2 Material Safety Data Sheet



Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

9. Physical and Chemical Properties

Appearance	colorless or colored
Physical state	sheets
Odor	odorless
Flash point	> 250 °C (ASTM D1929-68) > 482 °F (ASTM D1929-68)
pH-value	not applicable
Viscosity (dynamic)	not applicable
Specific gravity (water = 1)	1.19 g/cm ³ at 20 °C / 68 °F
Vapor density (air = 1)	not applicable
Vapor pressure	not applicable
Softening Temperature	from 103 °C / 217 °F
Boiling Temperature	not applicable
Solubility in water	insoluble
n-Octanol/water partition coefficient	not applicable
Evaporation rate	not applicable
Odor threshold	not available
Further information	none

See Section 5, Fire Fighting Measures

10. Stability and Reactivity

Stability

This product is stable under normal storage conditions.

Conditions To Avoid

This material is considered stable.

Incompatibility With Other Materials

No known incompatibility with other materials.

Hazardous Decomposition Products

In case of thermal decomposition, combustible vapors are formed, which are irritating to eyes and respiratory system, mainly consisting of: methyl methacrylate

Hazardous Polymerization

Product will not undergo polymerization.

11. Toxicological Information

Further Information on Toxicology

The product has not been tested toxicologically. When handled and used as directed the product will not cause hazardous effects to health according to studies on similar products and practical experience.



OP2 Material Safety Data Sheet

Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

12. Ecological Information

Information on Elimination (Persistence and Degradability)

Ecotoxicological Effect

Further Information on Ecology

The product has not been tested eco toxicologically.

On the basis of the products consistency as well as its low water solubility a bio availability is unlikely. Studies on products with similar composition confirm this assumption.

13. Disposal Considerations

Procedures

Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. CYRO encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste.

14. Transport Information

Further information

Not subject to the regulations on dangerous goods.

15. Regulatory Information

INVENTORY INFORMATION

EINECS (EU)	listed or exempted
TSCA (USA)	listed or exempted
DSL (CDN)	listed or exempted

US FEDERAL REGULATORY INFORMATION

Component / CASRN	TPQ [lbs]	CERCLARQ [lbs] (40CFR302.4)	SARA 302 List of EHS	SARA 313 (40CFR372)	TSCA 12b
NONE					

COMPONENT CLASSIFICATION UNDER CLEAN AIR ACT SECTION 112

Component / CASRN	Weight %	HAP	EHAP
NONE			

PRODUCT CLASSIFICATION UNDER SECTION 311/312 OF SARA (40CFR370)

NONE



OP2 Material Safety Data Sheet

Material Safety Data Sheet

Status: 07/08/2008

Version: 1.1

ACRYLITE® - Special Products

US STATE REGULATORY INFORMATION

Component / CASRN	New Jersey RTK	Pennsylvania RTK	Massachusetts RTK	California Proposition 65 Cancer	California Proposition 65 Reproductive
acrylic polymer / trade secret	NO	NO	NO	NO	NO

This product contains (a) chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

CANADIAN REGULATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation and the MSDS contains all information required by the Controlled Products Regulations.

This is a non-controlled product.

WHMIS: NO

Component / CASRN	NPRI
NONE	

16. Other Information

	Health	Flammability	Physical Hazard
HMIS-Ratings	0	1	0
NFPA-Ratings	0	1	0

HMIS Hazard Ratings

4 = severe
 3 = serious
 2 = moderate
 1 = slight
 0 = minimal
 N = no rating for powders
 * = chronic health hazard

NFPA Hazard Ratings

4 = extreme
 3 = high
 2 = moderate
 1 = slight
 0 = insignificant
 N = no rating for powders

This MSDS was prepared in accordance with ANSI Z400.1-1998.

Places marked by || have been amended from the last version.

This information and all further technical advice are based on Degussa's present knowledge and experience. However, Degussa assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, Degussa disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. DEGUSSA SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. Degussa reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

Date of printing : 07/24/2008



Service. It's what we deliver.

1.800.231.4175 www.acplasticsinc.com