I. PRODUCT AND COMPANY IDENTIFICATION

Product Name	Makrolon LD Light Diffusing White-B48, Smooth/Smooth	
Material Number:	83647885	
Chemical Family:	Thermoplastic Polymer Sheet	
Chemical Name:	Bisphenol A Polycarbonate	

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Caution: Form: solid sheets Odor: Odorless

Melted product is flammable and produces intense heat and dense smoke during burning. Irritating gases/fumes may be given off during burning or thermal decomposition. Causes a slipping hazard if spilled. Contact with hot material will cause thermal burns.

POTENTIAL HEALTH EFFECTS

PRIMARY ROUTES OF ENTRY	Inhalation, Skin Contact, Eye Contact
MEDICAL CONDITIONS	Respiratory disorders
AGGRAVATED BY EXPOSURE	

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE

SKIN

Acute Skin For Product: Makrolon LD Light Diffusing White-B48, Smooth/Smooth Contact with heated material can cause thermal burns.

EYE

Acute Eye For Product: Makrolon LD Light Diffusing White-B48, Smooth/Smooth May cause mechanical irritation.

INGESTION

Acute Ingestion For Product: Makrolon LD Light Diffusing White-B48, Smooth/Smooth Ingestion is not a typical route of industrial exposure.

GENERAL EFFECTS OF EXPOSURE

Acute Effects of Exposure For Product: Makrolon LD Light Diffusing White-B48, Smooth/Smooth Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.



It's what we deliver.

CHRONIC EFFECTS OF EXPOSURE

For Product: MAKROLON LD LIGHT DIFFUSING WHITE-B48, SMOOTH/SMOOTH

Not expected to cause any adverse chronic health effects.

Carcinogenicity:

No Carcinogenic substances as defined by IARC, NTP and/or OSHA

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

4. FIRST AID MEASURES

EYE CONTACT

In case of contact, flush eyes with plenty of lukewarm water.

SKIN CONTACT

Cool melted product on skin with plenty of water. Do not remove solidified product. Get medical attention if thermal burn occurs.

INHALATION

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

INGESTION

Get medical attention.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Water fog, Dry chemical, Carbon dioxide (CO2)

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.



It's what we deliver.

UNUSUAL FIRE/EXPLOSION HAZARDS

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Dust may form explosive mixtures with air.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES

If molten, allow material to cool and place into an appropriate marked container for disposal. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

STORAGE TEMPERATURE

Maximum: 49 °C (120.2 °F)

STORAGE PERIOD

Containers should be tightly closed to prevent contamination with foreign materials and moisture.

HANDLING/STORAGE PRECAUTIONS

Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Avoid creating dust.

FURTHER INFO ON STORAGE CONDITIONS

Protect equipment (e.g. storage bins, conveyors, dust collectors) with explosion vents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable

INDUSTRIAL HYGIENE/VENTILATION MEASURES

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines, especially during cutting, grinding and high heat operations.

RESPIRATORY PROTECTION

Although no exposure limit has been established for this product, the OSHA PEL for Particulates Not Otherwise Regulated (PNOR) of 15 mg/m3 – total dust, 5 mg/m3 – respirable fraction is recommended. In addition, the ACGIH recommends 3 mg/m3 – respirable particles and 10 mg/m3 – inhalable particles for Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS).



HAND PROTECTION

Wear heat resistant gloves when handling molten material.

EYE PROTECTION

Safety glasses with side-shields

SKIN AND BODY PROTECTION

No special skin protection requirements during normal handling and use.

ADDITIONAL PROTECTIVE MEASURES

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Purgings should be collected as small flat thin shapes or thin strands to allow for rapid cooling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: solid
Appearance: sheets

Appearance: sheets
Odor: Odorless

pH: not applicable

Melting Point: 220-230°C(428-446°F)

Density: ca. 1.2 g/cm3 @ 20 °C (68 °F) (DIN 53479) insoluble

Solubility in Water: > 450 °C (842 °F)

Autoignition temperature: >= 380 °C (716 °F)

Decomposition temperature: Fumes evolved by overheating during improperly processing or by

burning may be injurious to health.

Softening point: 150-160°C(302-320°F)

Viscosity, dynamic: not applicable



10. STABILITY AND REACTIVITY

HAZARDOUS REACTIONS

Hazardous polymerisation does not occur.

Stability: Stable

Conditions to avoid None known

Incompatible materials: None known

Hazardous decomposition products By Fire and Thermal Decomposition: Phenol; Carbon oxides,

Hazardous decomposition products due to incomplete combustion

II. TOXICOLOGICAL INFORMATION

Toxicity Data for MAKROLON LD LIGHT DIFFUSING WHITE-B48, SMOOTH/SMOOTH

Toxicity Note No data available for this product.

12. ECOLOGICAL INFORMATION

Ecological Data for MAKROLON LD LIGHT DIFFUSING WHITE-B48, SMOOTH/SMOOTH

Additional Ecotoxicological Remarks No data available for this product. The material is not a

contaminant for water or air. Material is not biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Waste disposal should be in accordance with existing federal, state

and local environmental control laws.

14. TRANSPORT INFORMATION

Land transport (DOT)	Non-Regulated
Sea transport (IMDG)	Non-Regulated
Air transport (ICAO/IATA)	Non-Regulated



It's what we deliver.

15. REGULATORY INFORMATION

United States Federal Regulations

OSHA Hazcom Standard Rating: Non-Hazardous

US. Toxic Substances Control Act: Excluded: Article.

US. EPA CERCLA Hazardous Substances (40 CFR 302):

Components None

SARA Section 311/312 Hazard Categories: Non-hazardous under Section 311/312

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302

Extremely Hazardous Substance (40 CFR 355, Appendix A):

Components None

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic

Chemicals (40 CFR 372.65) – Supplier Notification Required:

Components None

US. EPA RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) COMPOSITE LIST OF HAZARDOUS WASTES AND APPENDIX VIII HAZARDOUS CONSTITUENTS (40 CFR 261)

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

STATE RIGHT-TO-KNOW INFORMATION

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state. The concentrations reported below in units of parts per million (ppm) or parts per billion (ppb) are maximum values.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

Weight percent Components CAS-No.

>=1% Bisphenol A Polycarbonate 25971-63-5

>=1% Bisphenol A Polycarbonate CAS# is a trade secret

>=1% Bisphenol A Polycarbonate CAS# is a trade secret

MA Right to Know Extraordinarily Hazardous Substance List:

Weight percent Components CAS-No.
<10 ppm Phenol 108-95-2
<=3 ppm Methylene Chloride 75-09-2



California Prop. 65:

Warning! This product contains chemical(s) known to the State of California to be Carcinogenic.

Weight percent Components CAS-No. <=3 ppm Methylene Chloride 75-09-2

16. OTHER INFORMATION

HMIS Rating

Health (

Flammability

Physical Hazard 0

0=Minimal I=Slight 2=Moderate 3=Serious 4=Severe

* = Chronic Health Hazard

The method of hazard communication for A&C Plastics is comprised of Product Labels and Material Safety Data Sheets. HMIS and NFPA ratings are provided by A&C Plastics as a customer service.

Contact person: Product Safety Department

Telephone: (412) 777-2835 MSDS Number: 112000043651

Version Date: 03/06/2011

Report version: 1.1

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of A&C Plastics. The information in this MSDS relates only to the specific material designated herein. A&C Plastics assumes no legal responsibility for use of or reliance upon the information in this MSDS.

