

SDS - V-Cast Acrylic



1. PRODUCT NAME: V-CAST ACRYLIC

2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT DESCRIPTION

Clear, opal, color or transparent tinted sheet.
A high molecular weight acrylic sheet used in a wide range of applications.
Acrylic polymer based on methyl methacrylate.

CAS No.: 009010-88-2

HAZARDOUS INGREDIENT (S)

CAS No. symbol R Phrases

No classifiable hazardous ingredient(s).

3. HAZARDS IDENTIFICATION

Low toxicity under normal conditions of handling and use. Thermal decomposition will evolve toxic, irritant and flammable vapours. Care should be taken during thermoforming to ensure that the product is not exposed to temperatures exceeding 200 Deg C. Certain machining operations eg laser cutting, can give rise to toxic and corrosive fumes. Adequate ventilation MUST be used.

4. FIRST-AID MEASURES

Inhalation: Remove patient from exposure, keep warm and at rest.
Obtain medical attention if ill effects occur.

Skin Contact: Wash skin with soap and water.
If symptoms develop, obtain medical attention.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Ingestion: Do not induce vomiting. Obtain medical attention if ill effects occur.

Further Medical Treatment

Symptomatic treatment and supportive therapy as indicated.

5. FIRE-FIGHTING MEASURES

Combustion will evolve toxic, irritant and flammable vapours.

Extinguishing Media: Water spray, foam, dry powder or CO2.

Fire Fighting Protective Equipment: A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Offcuts, or dust should be collected and disposed of in a safe way.

SDS - V-Cast Acrylic



7. HANDLING AND STORAGE

7.1 HANDLING

These sheets are heavy and unwieldy. They should be handled with care, particularly in windy locations or outdoors. If broken or chipped the resultant edges can be sharp and cause cuts to skin and eyes. Take precautionary measures against static discharges.

Process Hazards

All polymers degrade to some extent at their processing temperature, an effect which increases with increasing temperature.

Under normal conditions where thermoforming temperatures will not exceed 200 Deg C thermal decomposition products will include methyl methacrylate. Certain machining operations eg laser cutting, can give rise to toxic and corrosive fumes.

Adequate ventilation **MUST** be used.

Other operations such as band saw cutting may give rise to strong odors.

7.2 STORAGE

Keep away from heat. Store vertically on A-frames

Storage Temperature: Below 40 Deg C

Storage Life: Indefinite under specified storage conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Local extraction close to the cutting head must be used when laser cutting. Where suitable engineering controls are not fitted or are inadequate, wear suitable protective equipment. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

The following information is given as general guidance.

- Respirators : **NORMAL HANDLING:** Not normally required.

PROCESSING:

Dust: A suitable dust mask or dust respirator with filter type P may be appropriate. (EN141/EN143)

Vapour: If high levels above the Occupational Exposure Limit are likely - A suitable mask with filter type A may be appropriate. (EN141/EN143)

- Eye Protection: Wear eye/face protection. Safety spectacles/goggles/full face shield.
- Gloves: Sharp edges may cause cuts. Wear suitable gloves.
- Other : Wear suitable protective clothing. For information regarding process hazards refer to Section 7, Handling and Storage.

The following values apply to substances which may be evolved during thermal processing.

SDS - V-Cast Acrylic



Occupational Exposure Limits

HAZARDOUS INGREDIENT(S)	LTEL 8hr TWA		STEL Time		
	ppm	mg/m3	ppm	mg/m3	
Methylmethacrylate (Methacrylic acid methyl ester)	50	250	100	410	OES

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Sheet.

Color: opal tint ,color or clear

Odor: odorless

PH (Value): Not applicable.

Boiling Point (Deg C): Not applicable.

Melting Point (Deg C): Not applicable.

Flash Point(Deg C):11.5(MMA).Sheet has no flash point.

Flammable Limits: Not applicable.

Smoke Density ,% (ASTM D2843-77): 5 max

Auto Ignition Temperature (Deg C): 421 (MMA).

Explosive Properties: Not applicable.

Oxidizing Properties: Not applicable.

Vapour Pressure (Pascals): Not applicable.

Density (g/ml): 1.19

Solubility (Water): insoluble

Solubility(Other): soluble in most organic solvents, acetone and chlorinated hydrocarbons

Partition Coefficient: Not applicable.

Freezing Point (Deg C): Not applicable.

Softening Point (Deg C): >100

10. STABILITY AND REACTIVITY

Hazardous Reactions: None known.

Hazardous Decomposition Product(s): Methyl methacrylate, ethyl acrylate, sulfides, and traces of Acrolein.

11. TOXICOLOGICAL INFORMATION

Inhalation: Unlikely route of exposure.

Skin Contact: No evidence of irritant effects from normal handling and use. Sharp edges may cause cuts.

Eye Contact: Swarf or dust may cause irritation. Sharp off-cuts may cause eye damage.

Ingestion: Unlikely to be hazardous if swallowed.

Long Term Exposure: No known hazards are associated with the use of this material.

SDS - V-Cast Acrylic



12. ECOLOGICAL INFORMATION

This environmental hazard assessment is based on information available on similar products.

Environmental Fate and Distribution

High tonnage material produced in partially contained systems. Solid with low volatility. The product is essentially insoluble in water. The product has low potential for bioaccumulation. The product has low mobility in soil.

Persistence and Degradation

The product is non-biodegradable in soil. There is no evidence of degradation in soil and water.

Toxicity

The product is predicted to have low toxicity to aquatic organisms.
WGK 0(self classification)

Effect on Effluent Treatment

Unlikely to have an effect on effluent treatment system. The material is essentially insoluble in water and can therefore be separated from aqueous medium by sedimentation and filtration processes at an effluent treatment plant.

13. DISPOSAL CONSIDERATIONS

Large quantities of waste may be recoverable. Contact supplier for specialized advice. Disposal should be in accordance with local, state or national legislation. Incineration may be used to recover energy value. Bury on an authorized landfill site or incinerate under approved controlled conditions.

14. TRANSPORT INFORMATION

Not Classified as Dangerous for Transport.

15. REGULATORY INFORMATION

Not Classified as Dangerous for Supply/Use.

EC Classification: Under the Classification, Packaging and Labeling of Dangerous Substances Regs, 1984, this material is not dangerous for supply or conveyance.

16. OTHER INFORMATION

This data sheet was prepared in accordance with Directive 93/112/EC.



16. OTHER INFORMATION (continued)

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. We give no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. We accept no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, and Designs cannot be assumed.

A&C Plastics has no control over the conditions under which this material is used and therefore does not guarantee that results described herein will be achieved. Each user is responsible for conducting their own tests to determine the material's suitability for their specific application. A&C Plastics and its distributors assume no liability for losses resulting from improper installation or use of the material. As part of our policy of continuous product development, please verify with A&C Plastics that you have the most current information available.

GLOSSARY

OES: Occupational Exposure Standard (UKHSEEH40)

MEL: Maximum Exposure Limit (UKHSEEH40)

LTTEL: Long Term Exposure Limit

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

SK: Can be absorbed through skin