

Product Data - OPTIX Acrylic Nonglare Heavy Matte



OPTIX NG Heavy Matte is a non-glare translucent acrylic sheet. Unlike glass, it's shatter-resistant and lightweight, which makes it ideal for indoor and outdoor glazing in large frames or any situation where shattering glass would be a safety concern.

APPLICATIONS

Signage, silk-screening, and point-of-purchase displays

TYPICAL PROPERTIES*

Property	Test Method	Units	Values
PHYSICAL			
Specific Gravity/Relative Density	ASTM D 792	—	1.19
Water Absorption	ASTM D 570	%	0.4
MECHANICAL			
Tensile Strength	ASTM D 638	psi	11,030
Tensile Modulus of Elasticity	ASTM D 638	psi	490,000
Flexural Strength	ASTM D 790	psi	17,000
Izod Impact Strength – Notched	ASTM D 256	ft-lb/in	0.4
THERMAL			
Maximum Recommended Continuous Service Temperature	—	°F	170-190
Deflection Temperature @ 264 psi (1.8 MPa)	ASTM D 648	°F	203
Deflection Temperature @ 66 psi (0.45 MPa)	ASTM D 648	°F	207
Coefficient of Thermal Expansion	ASTM D 696	in/in/°F	3.0x10 ⁻⁵
Flammability (Burning Rate)	ASTM D 635	in/minute	1.0
Flammability	UL 94	—	HB
Smoke Density Rating	ASTM D 2843	%	3.4
Self-Ignition Temperature	ASTM D 1929	°F	833

*Typical properties are not intended for specification purposes

These data are presented only as typical properties of the base resins which, to our best knowledge, are true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guaranty or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise. All risks of such use are assumed by the user. Furthermore, nothing contained herein shall be construed as an inducement or recommendation to use any process or to manufacture or use any product in conflict with existing or future patents.