1. Identification

TRANSPORTATION EMERGENCY

CALL CHEMTREC: INTERNATIONAL: (800) 424-9300 (703) 527-3887

NON-TRANSPORTATION

Emergency Phone: Information Phone: Call Chemtrec (844) 646-0545

Product Name: Material Number: Chemical Family: Use: MAKROLON SL SUNLIFE CLEAR-A00, SMOOTH / SMOOTH 58092480 Thermoplastic Polymer Sheet For the production of plastic sheet products

2. Hazards Identification

GHS Classification

This product is not hazardous in the form in which it is shipped by the manufacturer.

| GHS Label Elements Signal word: | Warning |
|---|--|
| Hazard statements: | If fine particles are generated during further processing, handling or by other means, product may form combustible dust concentrations in air. |

3. Composition/Information on Ingredients

Hazardous Components

There are no hazardous components above the relevant concentration limits according to OSHA HazCom 2012.

4. First Aid Measures

Most Important Symptom(s)/Effect(s)

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.



Eye Contact

In case of contact, flush eyes with plenty of lukewarm water.

Skin Contact

Cool melted product on skin with plenty of water. Do not remove solidified product. Get medical attention if thermal burn occurs.

Inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

Ingestion

Get medical attention.

5. Firefighting Measures

Suitable Extinguishing Media: Water fog, Dry chemical, Carbon dioxide (CO2), Foam

Unsuitable Extinguishing Media: High Pressure Water Streams

Fire Fighting Procedure

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: ; Phenol Carbon oxides, Hazardous decomposition products due to incomplete combustion

Unusual Fire/Explosion Hazards

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Avoid generating dust: fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard.

6. Accidental Release Measures

Spill and Leak Procedures

If molten, allow material to cool and place into an appropriate marked container for disposal. Sweep up and shovel into suitable containers for disposal. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture as they are released into the atmosphere in sufficient concentrations. Avoid dispersal of dust in the air (e.g., cleaning dust from surfaces with compressed air).

7. Handling and Storage

Handling/Storage Precautions

Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces. Solid particulate can generate electrical charging during operations such as unloading from containers and pneumatic transfer. Provide adequate precautions, such as electrical grounding and bonding, where conductive equipment is involved.



Storage Period: None.

Storage Temperature Maximum:

49 °C (120.2 °F)

Storage Conditions

Containers should be tightly closed to prevent contamination with foreign materials and moisture.

Substances to Avoid

None known.

8. Exposure Controls/Personal Protection

Exposure Limits

Country specific exposure limits have not been established or are not applicable

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

Industrial Hygiene/Ventilation Measures

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines, especially during cutting, grinding and high heat operations.

Respiratory Protection

Although no exposure limit has been established for this product, the OSHA PEL for Particulates Not Otherwise Regulated (PNOR) of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction is recommended. In addition, the ACGIH recommends 3 mg/m3 - respirable particles and 10 mg/m3 - inhalable particles for Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS).

Hand Protection

Wear heat resistant gloves when handling molten material.

Eye Protection

Safety glasses with side-shields

Skin Protection

No special skin protection requirements during normal handling and use.

Additional Protective Measures

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Purgings should be collected as small flat thin shapes or thin strands to allow for rapid cooling.

9. Physical and Chemical Properties

State of Matter: Appearance: Color: solid Sheet Clear



Makrolon SL Safety Data Sheet

Odor: **Odor Threshold:** Odorless pH: No Data Available Melting Point: No Data Available **Boiling Point:** 220 - 230 °C (428 - 446 °F) Flash Point: No Data Available **Evaporation Rate:** No Data Available Flammability: No Data Available Lower explosion limit: No Data Available **Upper Explosion Limit:** No Data Available Vapor Pressure: No Data Available Vapor Density: No Data Available **Density:** No Data Available **Relative Vapor Density:** ca. 1.2 g/cm³ @ 20 °C (68 °F) (DIN 53479) **Specific Gravity:** No Data Available Solubility in Water: No Data Available Partition Coefficient: ninsoluble octanol/water: No Data Available Auto-ignition Temperature: > 450 °C (842 °F) **Decomposition Temperature:** $>= 380 \,^{\circ}\text{C} (716 \,^{\circ}\text{F})$ Fumes evolved by overheating during improperly processing or by burning may be injurious to health. Softening point: 150 - 160 °C (302 - 320 °F) not applicable

No Data Available

Dynamic Viscosity: Kinematic Viscosity:

10. Stability and Reactivity

Hazardous Reactions

Hazardous polymerisation does not occur.

Stability Stable

Materials to Avoid None known.

Conditions to Avoid

Generation of dust clouds.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: Phenol; Carbon oxides, Hazardous decomposition products due to incomplete combustion

11. Toxicological Information

Likely Routes of Exposure:

Inhalation Skin Contact Eye Contact

Health Effects and Symptoms

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.



Makrolon SL Safety Data Sheet

Toxicity Data for: MAKROLON SL SUNLIFE CLEAR-A00, SMOOTH / SMOOTH

No data available for this product.

Carcinogenicity:

No carcinogenic substances as defined by IARC, NTP and/or OSHA

12. Ecological Information

Ecological Data for: MAKROLON SL SUNLIFE CLEAR-A00, SMOOTH / SMOOTH

No data available for this product.

13. Disposal Considerations

Waste Disposal Method

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

14. Transportation Information

Land transport (DOT) Non-Regulated

<u>Sea transport (IMDG)</u> Non-Regulated

<u>Air transport (ICAO/IATA)</u> Non-Regulated

15. Regulatory Information

<u>United States Federal Regulations</u> US. Toxic Substances Control Act: Excluded: Article.

No substances are subject to TSCA 12(b) export notification requirements.

US. EPA CERCLA Hazardous Substances (40 CFR 302) Components: None

SARA Section 311/312 Hazard Categories: Non-hazardous under Section 311/312

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components: None



Makrolon SL Safety Data Sheet

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components: None

US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

The concentrations reported below in units of parts per million (ppm) or parts per billion (ppb) are maximum values.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

| Weight percent | Components | CAS-No. | | |
|---|--|-------------------------|--|--|
| >=1% | Bisphenol A Polycarbonate | 25971-63-5 | | |
| >=1% | Bisphenol A Polycarbonate | CAS# is a trade secret | | |
| >=1% | Bisphenol A Polycarbonate | CAS# is a trade secret | | |
| Massachusetts Right to Know Extraordinarily Hazardous Substance List: | | | | |
| Massachusetts Right to | o Know Extraordinarily Hazardous Subs | stance List: | | |
| Massachusetts Right to Weight percent |) Know Extraordinarily Hazardous Sub Components | stance List: CAS-No. | | |
| | • | | | |

California Prop. 65:

Warning! This product contains chemical(s) known to the State of California to be Carcinogenic. Female reproductive toxin.

| Weight percent | Components | CAS-No. |
|----------------|--------------------|---------|
| <=3 ppm | Methylene Chloride | 75-09-2 |
| Trace element | Bisphenol A | 80-05-7 |

